



**Safety Data Sheet  
CONKLIN COMPANY, INC.**

Date Prepared: 1/2/2023

SDS Number: 3012

**SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

|   |   |
|---|---|
| <b>Product Identifier</b><br>Power Mate (Aerosol)   | <b>General Use</b><br>Heavy-Duty Engine Degreaser   |
| <b>Manufacturer's Name</b><br>Conklin Company   | <b>Emergency Telephone Numbers</b><br>Health: (888) 786-0974 Transport: (800) 424-9300              |
| <b>Address (Number, Street, City, State and Zip)</b><br>551 Valley Park Drive<br>Shakopee, MN 55379 | <b>Phone Number for Additional Information</b><br>(952) 445-6010<br><b>Website:</b> www.conklin.com |

**SECTION 2 - HAZARDS IDENTIFICATION**

|                           |   |
|---------------------------|---|
| <b>Signal Word:</b>       | <b>Danger</b>   |
| <b>Hazard statements:</b> | <p><b>Toxic if swallowed or inhaled.</b></p> <p><b>Aspiration hazard: May be fatal if swallowed and enters airways.</b></p> <p><b>May be absorbed through skin.</b></p> <p><b>Causes skin irritation and serious eye irritation.</b></p> <p><b>Extremely flammable aerosol.</b></p> <p><b>Contains gas under pressure; may explode if heated.</b></p> |

**Precautions:** Keep away from heat, sparks, pilot lights, open flames, static electricity, or other sources of heat or ignition. - No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Avoid breathing mist, vapors and spray.  
Use only outdoors or in a well ventilated area.  
Do not eat, drink or smoke when using this product.  
Wear gloves, safety glasses or goggles, and long-sleeved clothing when handling.  
Wash hands thoroughly after handling.

**Response:** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice or attention.  
If swallowed: Immediately call a physician or Poison Control Center.  
Rinse Mouth.  
If on skin: Wash with plenty of soap and water.  
If skin irritation occurs: Get medical advice or attention.  
Immediately take off all contaminated clothing and wash it before reuse.  
If inhaled: Remove person to fresh air and keep comfortable for breathing.  
Immediately call a physician or Poison Control Center.

**Potential Health Effects, Based on Individual Components (May Vary Among Individuals)**

- Eye:** Will cause eye irritation. Compressed liquid may cause freeze-burns.
- Skin:** Compressed liquid may cause freeze-burns. Avoid skin contact. May cause skin irritation.
- Ingestion:** Harmful or fatal if swallowed. May cause mouth, throat and stomach irritation.
- Inhalation:** Asphyxiant. Prolonged exposure may cause nausea, dizziness, headaches at low concentrations. Aspiration into lungs may cause chemical pneumonia. May cause damage to liver, kidney, blood system, and central nervous system.

Causes damage to Blood, Central Nervous System, Eyes, Gastrointestinal Tract, Hematopoietic System, Kidneys, Liver, Lungs, Lymphatic System, Respiratory System, and Skin through prolonged or repeated exposure.

**Medical conditions aggravated by exposure:**

None known

**Chronic effect** See Section 15 for California Proposition 65 information.

**SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS**

| Component                                   | CAS Number | Percent by Weight |
|---|------------|-------------------|
| Methyl Acetate                              | 79-20-9    | 50% to 60%        |
| Petroleum gas (liquefied) (A-70 propellant) | 68476-85-7 | 20% to 30%        |
| Distillates (petroleum), hydrotreated light | 64742-47-8 | 10% to 20%        |
| Methyl Ethyl Ketone                         | 78-93-3    | 5% to 10%         |
| 2-Butoxy ethanol                            | 111-76-2   | 1% to 5%          |
| Dimethylformamide                           | 68-12-2    | 0.1% to 1.0%      |

See Section 8 for exposure guidelines.

**SECTION 4 - FIRST AID MEASURES**

**EYES:** Quickly and gently blot or brush chemical off the face. Immediately flush the contaminated eye(s) with clean, lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens until after flushing is complete. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately obtain medical attention.

**SKIN:** Remove contaminated clothing, shoes, and leather goods (e.g. watchbands, belts). Flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, repeat flushing. Obtain medical advice. Completely decontaminate clothing, shoes, and leather goods before reuse, or discard. Get immediate medical attention if injected into or under the skin, or into any part of the body. The individual should be evaluated immediately by a physician as a surgical emergency, regardless of the appearance of the wound or its size. Even though initial symptoms may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of the injury.

**INGESTION:** Never give anything by mouth to a victim who is rapidly losing consciousness, is unconscious, or is convulsing. Have victim rinse mouth thoroughly with water. Do NOT induce vomiting. Have victim drink a glass of water (2 to 8 ounces or 60 to 240 mL). Immediately obtain medical attention.

**INHALATION:** This product is (extremely) flammable. Take proper precautions (e.g. remove any sources of ignition). Remove source of contamination or move victim to fresh air. Obtain medical advice.

**SECTION 5 - FIRE FIGHTING MEASURES**

**FLASH POINT:** For propellant -156°F (LEL 1.8; UEL 9.5)

**EXINGUISHING MEDIA:** Foam, dry chemical, CO<sub>2</sub>.

**SPECIAL FIRE FIGHTING PROCEDURES:** Aerosol containers may explode when heated. Limit use of water spray to cool containers and to protect personnel. Water may not be effective to extinguish a fire involving this material. Vapors are heavier than air and may be ignited after traveling considerable distances, causing flashback or explosion. Firefighters should use approved self-contained breathing apparatus and full turn-out (Bunker) gear when fighting fires involving chemicals, to protect against possible toxic fumes or vapors. Cool and use caution when approaching fire-exposed containers.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

**SPILL OR LEAK PROCEDURE:** Use personal protection recommended in Section 8. Remove all sources of ignition, including sparks and static electricity. Use non-sparking, explosion-proof tools and equipment. Do not vacuum. Ventilate area thoroughly. Stay upwind. Isolate area from unprotected personnel. Dike to prevent spill from spreading. Collect with compatible absorbent material and place in metal container with tight fitting cover. Floor may be slippery - use care and clean thoroughly. Keep out of sewer, septic system, ground water, and open waters. Notify federal, state and local authorities, as applicable.

## SECTION 7 - HANDLING AND STORAGE

**STORAGE TEMPERATURE:** Store above 40°F and below 80°F.

**HANDLING AND STORAGE PRECAUTIONS:** Use personal protection recommended in Section 8. Do not cut, weld, drill, or otherwise expose empty or full containers to heat, sparks, pilot lights, open flames, static electricity, or other sources of heat or ignition. Open containers slowly in case of pressure accumulation. Bond and ground containers and equipment during transfer. Vapors are/may be heavier than air and may cause ignition away from storage or handling location. Use non-sparking tools. Protect from direct sunlight. Store in dry, cool, ventilated area in tightly closed containers out of the reach of children. Do not store on side. Avoid creasing or impacting container sidewalls. Empty containers may be hazardous. Do not eat, drink, or smoke in chemical use or storage areas. Wash hands after handling and before eating, drinking, or smoking. Do not rub eyes with soiled hands. See Section 10 for metals or other materials to avoid.

## SECTION 8 - PERSONAL PROTECTION/EXPOSURE CONTROLS

**ENGINEERING CONTROLS:** Provide sufficient general and local explosion-proof exhaust ventilation to maintain safe exposure levels. Take measures to minimize exposure. Provide a source of clean water for flushing eyes and skin.

**EYE PROTECTION REQUIREMENTS:** Use ANSI-approved eye protection (e.g. safety glasses, goggles), as required by work conditions. Use ANSI-approved chemical splash goggles and face shield if splashing may occur.

**SKIN PROTECTION REQUIREMENTS:** Chemical-resistant gloves and clothing, as needed, to prevent skin contact. Wash hands before eating, drinking, or smoking.

**RESPIRATORY PROTECTION:** To protect against inhalation, a NIOSH-approved air-purifying respirator with organic vapor cartridges and dust/mist pre-filters may be permissible. Use a dust/mist filter or pre-filter if spraying. Use a positive pressure air-supplied respirator for unknown or uncontrolled situations, or when air-purifying respirators may not provide adequate protection.

## AIRBORNE EXPOSURE LIMITS

| Components                                  | OSHA<br>PEL/TWA                         | ACGIH<br>TLV/TWA     | STEL    |
|---|---|----------------------|---------|
| Methyl Acetate                              | TWA 200 ppm (610 mg/m <sup>3</sup> )    |                      |         |
| Petroleum gas (liquefied) (A-70 propellant) | TWA 1000 ppm (1800 mg/m <sup>3</sup> )  |                      |         |
| Distillates (petroleum), hydrotreated light | TWA 100 mg/m <sup>3</sup>               | 10 mg/m <sup>3</sup> |         |
| Methyl Ethyl Ketone                         | TWA 200 ppm (590 mg/m <sup>3</sup> )    | TWA 200 ppm          | 300 ppm |
| 2-Butoxy ethanol                            | TWA 50 ppm (240 mg/m <sup>3</sup> ) (s) |                      |         |
| Dimethylformamide                           | TWA 10 ppm (30 mg/m <sup>3</sup> ) (s)  |                      |         |

Definitions:

PEL = Permissible Exposure Limit

TLV = Threshold Limit Value

TWA = Time-weighted average (8 hour day)

STEL = Short term exposure limit (15 minutes), no more than 60 min./day

(c) = Ceiling (not to be exceeded under any condition)

(s) = Skin

---

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

|                |                  |                                       |                |
|----------------|------------------|---------------------------------------|----------------|
| Physical Form: | Liquid           | Solubility in Water:                  | Insoluble      |
| Color:         | Clear, colorless | Specific Gravity (Water = 1):         | 0.86 - 0.89    |
| Odor:          | Solvent          | Evaporation Rate (Butyl Acetate = 1): | > 1            |
| Boiling Range: | Not determined   | Vapor Pressure (mm Hg):               | Not determined |
| pH:            | Not applicable   | Vapor Density (Air = 1):              | < 1            |
| VOC:           | 48.5% by weight  |                                       |                |

---

**SECTION 10 – REACTIVITY**

|   |   |
|---|---|
| Stability:                              | Stable under anticipated storage and handling conditions.                         |
| Hazardous Polymerization:               | Will not occur.   |
| Incompatibilities (Materials to Avoid): | Avoid strong oxidizers, such as chlorine, open flames, sparks and excessive heat. |
| Hazardous Decomposition Products:       | Carbon monoxide, carbon dioxide, nitrogen oxides and hydrogen chloride gas.       |

---

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Product not tested as a whole. Refer to Section 3 for potential health effects.

---

**SECTION 12 – ECOLOGICAL INFORMATION**

Product not tested as a whole. Refer to Section 6 for information regarding accidental releases. Keep out of trash, water, sewer, and drainage systems.

---

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Do not burn or dispose of aerosol containers in fire. Recycle or dispose of contents and empty containers according to federal, state and local regulations. Keep out of trash, water, sewer, and drainage systems.

---

**SECTION 14 - TRANSPORTATION INFORMATION**

UN1950, Aerosol, flammable, 2.1

Exceptions: Limited Quantity, (not more than 1 liter)

Not packaged for Air or Vessel Transport

For additional information, please call the Transportation Department at (952) 445-6010.

---

**SECTION 15 - REGULATORY INFORMATION**

California Proposition 65 statement:

**WARNING:** This product can expose you to chemicals including Dimethylformamide (0.1% to 1.0%), which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

This product contains the following chemical(s) subject to the reporting requirements of SARA Title III, Section 313 (40 CFR Part 372): 2-Butoxy ethanol: 1% to 5%; Methyl Ethyl Ketone: 5% to 10%. CERCLA RQ = 5000 lbs (Methyl Ethyl Ketone).

---

**SECTION 16 - OTHER INFORMATION**

This document replaces the 1/2/2020 version. All Safety Data Sheets reviewed for composition and regulatory status.

---

The information contained in this Safety Data Sheet is based on data available to us from suppliers, and is believed to be true and correct; however, Conklin makes no warranty, express or implied, regarding the accuracy of this data or results obtained from the use of this product. Conklin and its employees assume no responsibility for injury or damage from the use of this product.