



**Safety Data Sheet
CONKLIN COMPANY, INC.**

Date Prepared: 1/2/2023

SDS Number: 4055

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier Butyl Tape	General Use Roofing seam sealer
Manufacturer's Name Conklin Company	Emergency Telephone Numbers Health: (888) 786-0974 Transport: (800) 424-9300
Address (Number, Street, City, State and Zip) 551 Valley Park Drive Shakopee, MN 55379	Phone Number for Additional Information (952) 445-6010 Website: www.conklin.com

SECTION 2 - HAZARDS IDENTIFICATION

Hazard statements: May cause skin irritation.
--

Precautions: Wear gloves and long-sleeved clothing when handling.
Wash hands thoroughly after handling.

Response: If on skin: Wash with plenty of soap and water.
If skin irritation occurs: Get medical advice or attention.
Take off contaminated clothing and wash it before reuse.

Potential Health Effects, Based on Individual Components (May Vary Among Individuals)**Eye:** Not expected to cause irritation under normal use.**Skin:** May cause irritation.**Ingestion:** Not expected to cause irritation under normal use.**Inhalation:** Not expected to cause irritation under normal use.

Causes damage to Eyes, Reproductive System, Respiratory System, and Skin through prolonged or repeated exposure.

Medical conditions aggravated by exposure:

None known

Chronic effect Not known to contain component(s) at 0.1% or greater listed as a carcinogen or possible carcinogen.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS Number	Percent by Weight
Calcium Carbonate	1317-65-3	30% to 40%

See Section 8 for exposure guidelines.

SECTION 4 - FIRST AID MEASURES

EYES: Do not rub eye(s). Let the eye(s) water naturally for a few minutes. Have victim look right and left, then up and down. If particle/dust does not dislodge, gently flush with clean, lukewarm, gently flowing water for 5 minutes or until particle/dust is removed, while holding the eyelid(s) open. If irritation persists, immediately obtain medical attention. DO NOT attempt to manually remove anything stuck to the eye.

SKIN: No health effects expected. If irritation does occur, flush with lukewarm water, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.

INGESTION: If irritation or discomfort occurs, obtain medical advice.

INHALATION: If symptoms are experienced, remove source of contamination or move victim to fresh air. Obtain medical advice.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: >200°F

EXINGUISHING MEDIA: Foam, dry chemical, CO₂.

SPECIAL FIRE FIGHTING PROCEDURES: Limit use of water spray to cool containers and to protect personnel. Water may not be effective to extinguish a fire involving this material. Vapors are heavier than air and may be ignited after traveling considerable distances, causing flashback or explosion. Firefighters should use approved self-contained breathing apparatus and full turn-out (Bunker) gear when fighting fires involving chemicals, to protect against possible toxic fumes or vapors. Cool and use caution when approaching fire-exposed containers.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURE: Collect for reuse, recycling, or proper disposal.

SECTION 7 - HANDLING AND STORAGE

STORAGE TEMPERATURE: Store above 40°F and below 100°F.

HANDLING AND STORAGE PRECAUTIONS: Store in dry, cool area away from open flames, sparks, or oxidizers.

SECTION 8 - PERSONAL PROTECTION/EXPOSURE CONTROLS

ENGINEERING CONTROLS: Provide sufficient general and local exhaust ventilation to maintain safe exposure levels. Take measures to minimize exposure. Provide a source of clean water for flushing eyes and skin.

EYE PROTECTION REQUIREMENTS: Use ANSI-approved eye protection (e.g. safety glasses, goggles), as required by work conditions. Use ANSI-approved chemical splash goggles and face shield if splashing may occur.

SKIN PROTECTION REQUIREMENTS: Chemical-resistant gloves and clothing, as needed, to prevent skin contact. Wash hands before eating, drinking, or smoking.

RESPIRATORY PROTECTION: Not required in normal uses.

AIRBORNE EXPOSURE LIMITS

Components	OSHA PEL/TWA	ACGIH TLV/TWA	STEL
Calcium Carbonate* *as dust	TWA 10 mg/m ³ (total) TWA 5 mg/m ³ (resp)		

Definitions:

PEL = Permissible Exposure Limit

TLV = Threshold Limit Value

TWA = Time-weighted average (8 hour day)

STEL = Short term exposure limit (15 minutes), no more than 60 min./day

(c) = Ceiling (not to be exceeded under any condition)

(s) = Skin

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical Form:	Tacky tape	Solubility in Water:	Insoluble
Color:	Gray	Specific Gravity (Water = 1):	1.25
Odor:	Mild rubber odor	Evaporation Rate (Butyl Acetate = 1):	Not applicable
Boiling Range:	Not Applicable	Vapor Pressure (mm Hg):	Not applicable
pH:	Not applicable	Vapor Density (Air = 1):	Not applicable
VOC:	Not applicable		

SECTION 10 – REACTIVITY

Stability:	Stable under anticipated storage and handling conditions.
Hazardous Polymerization:	Will not occur.
Incompatibilities (Materials to Avoid):	Avoid strong oxidizers and excessive heat.
Hazardous Decomposition Products:	Carbon monoxide, carbon dioxide, and nitrogen oxides.

SECTION 11 - TOXICOLOGICAL INFORMATION

Product not tested as a whole. Refer to Section 3 for potential health effects.

SECTION 12 – ECOLOGICAL INFORMATION

Product not tested as a whole. Refer to Section 6 for information regarding accidental releases. Keep out of trash, water, sewer, and drainage systems.

SECTION 13 - DISPOSAL CONSIDERATIONS

Recycle or dispose of contents and empty containers according to federal, state and local regulations. Keep out of trash, water, sewer, and drainage systems.

SECTION 14 - TRANSPORTATION INFORMATION

Not a DOT Hazardous Material.

SECTION 15 - REGULATORY INFORMATION

California Proposition 65 statement: This product does NOT contain chemicals known to the State of California to cause cancer and/or birth defects or other reproductive harm.

Does not contain any chemicals subject to the reporting requirements of SARA Title III, Section 313 (40 CFR Part 372) above de minimis concentrations.

SECTION 16 - OTHER INFORMATION

This document replaces the 1/2/2020 version. All Safety Data Sheets reviewed for composition and regulatory status.

The information contained in this Safety Data Sheet is based on data available to us from suppliers, and is believed to be true and correct; however, Conklin makes no warranty, express or implied, regarding the accuracy of this data or results obtained from the use of this product. Conklin and its employees assume no responsibility for injury or damage from the use of this product.