

CONKLIN ROOFING SYSTEMS PUMA® XL 20 YEAR NDL WARRANTY



Conklin Roofing Systems NDL is a No Dollar Limit Warranty. All systems must be installed per Conklin specifications. Conklin NDL Designated Contractors are independent contractors eligible to install and repair Conklin NDL Warranted roofs.

PUMA® XL Polyurethane Modified Acrylic Roof Coating

Product Description:

Basic use: PUMA® XL is an advanced-technology premium polyurethane modified acrylic roof coating with a highly reflective bright white finish. It is designed as a two coat waterproofing application using Benchmark® base coat. PUMA XL can be applied to metal roofs, spray polyurethane foam and Conklin's Fabric Reinforced System.

Testing & Approvals:

| | |
|---------------------------|-------------------------|
| UL-790 Fire Rating | Class "A" |
| Hail Data | UL Class "4" TGFU.R8435 |
| CRRC | Approved |

Technical Data:

| | |
|--|---|
| Color | White |
| Coverage | 1.9 gallons per 100 sq. ft. |
| Density | 10.9 lbs./Gallon |
| Thickness | 13.5 dry mils per coat |
| Number of Coats | Base & Top Coat |
| Dry Time** | 2-8 Hours |
| Total Solids: (by weight): (by volume): | 63.0% 52.0% |
| Elongation | 250% (Base & Top) ASTM D-412 |
| Tensile Strength | 360 psi (Base & Top) ASTM D-412 |
| Flexibility | Pass 1/8" Mandrel - 40 ° F ASTM D-1737 |
| Standard Test Method for Acrylic coatings | Pass-ASTM D6083-05 |
| Initial Reflectivity: Aged Reflectivity: | 0.86 - ASTM E-903 Pending |
| Initial Emissivity: Aged Emissivity: | 0.9 Pending |
| Initial SRI: Aged SRI: | 109 Pending |
| VOC Content | 46 g/L (0.39 lbs./gal) |

Contact Information for Conklin Roofing Systems Warranty Department

551 Valley Park Drive Shakopee, MN 55379
Phone 952-496-4218 Email joy.schmidt@conklin.com