

# Affinity™

## Polyurethane Roof Coating

### Manufacturer:

Conklin Company Inc.  
551 Valley Park Drive  
Shakopee, Minnesota 55379  
(800) 888 – 8838 Fax (952) 496 - 4285

### Product Description:

**Basic use:** Affinity™ is a polyurethane roof coating with a highly reflective bright white finish. It is designed as a waterproofing coating for metal, approved membranes, and concrete.

**Limitations:** Must not be applied at temperatures below 40°F or during inclement weather. Surface temperature must be at least 5°F above dew point and relative humidity less than 80 percent to ensure dry surfaces. Mix thoroughly before use. Ambient temperature should not exceed 100°F and surface temperature should not exceed 120° F. The polyurethane foam must be free of ponding water. A roof surface which has more than 36 sq. ft. of water in any area ¼” deep or more, 48 hours after a rain, shall be considered unacceptable. Small “bird baths” cannot account for more than 5 percent of the entire roof surface.

**Sizes:** Available in a 5 gallon container and 1 gallon containers in a case of 4.

**Coverage Rate:** Affinity should be applied at 1.1 gallons per 100 square feet.

### Technical Data:

Resin Type	Urethane
Color	White
Coverage	1.1 gallons per 100 sq. ft.
Density	10.2 lbs./Gallon
Thickness	13.5 dry mils
Number of Coats	Top Coat
Dry Time**	2-8 Hours
Total Solids (by weight):	As mixed 80%
(by volume):	71%
Elongation	600% (ASTM D-2370)
Tensile Strength	2000 psi (ASTM D-2370)
VOC Content	244g/L (2.0 lbs./gal)

\*\*Dry time for Affinity will vary depending on temperature, humidity, thickness at which the product is applied and wind. Lower wind speed, higher humidity or higher wet film thickness will increase the dry time in excess of the reported average.

### Application:

**Mixing/thinning:** Always mix Affinity and color packet thoroughly before use.

**Surface Preparation:** The substrate must be structurally sound, solid, clean and dry. On certain decks and surfaces, proper installation of drains, vapor retarders, roofing vents, expansion joints, flashings, and positive slope to drain will be required.

The application surface must be finished, smooth and free of grease, wax, dirt, contaminants, moisture and other matter that would interfere with adhesion. It must also be free of chips loose roofing or other foreign matter.

Do not apply to SPF foam surfaces with texture of “verge popcorn” “popcorn” or “tree bark”.

**NOTE:** This product has no fire rating.

# Affinity™

## Polyurethane Roof Coating

**Application:** The recommended application rate is 1.1 gallons per 100 sq. ft. of Affinity top coat. This rate includes 15 percent for application loss and 10 percent for surface texture. Under very irregular roofing substrate conditions more product may be required. Must be applied in a continuous, unbroken film of dry thickness no less than 13.5 mils per coat over entire roof. If roofing granules are to be used, they **MUST** be embedded using a second application of top coat at 1.0 gallon per 100 sq. ft. Quartz granules should be applied at a minimum of 50 lbs. per 100 sq. ft.

### Clean Up:

While coating is still wet, clean tools and the area with xylene.

### Disposal:

Dispose of product in accordance with local state and federal regulations governing hazardous waste.

### Safety:

**Warning:** HARMFUL IF SWALLOWED. May cause eye, skin and respiratory system irritation. Keep out of the reach of children. If spraying use a NIOSH-approved dust/mist mask.

**First Aid:** Eyes – immediately flush with plenty of water for at least 15 minutes. If a contact lens is present, **DO NOT** delay irrigation or attempt to remove the lens until flushing is complete. Skin – wash with soap and water, followed by a thorough rinse. Ingestion – if swallowed, **DO NOT INDUCE VOMITING**, dilute with three to four glasses of water. Immediately call a Poison Control Center or physician for further instructions. Inhalation – immediately move to fresh air.

For US Health Hazard Information, call:

**1-888-786-0974**

**Proposition 65 Statement:** This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

### Storage:

Keep containers tightly closed when not in use. Store in a cool place, above 40° F. Keep from freezing.

**Please Note:** *Previous field- applied coatings and residential properties are not warrantable.*

