

# ACCLAIM POND B GONE™

## Two Part Urethane Slope Correction

### Technical Data:

Resin Type	Urethane
Color	Gray
Coverage	16 square feet at 1/4" deep, 8 square feet at 1/2" deep, 4 square feet at 1" deep
Density	9.8 lbs./Gallon
Number of Coats	1
Open Working Time	10 minutes once poured
Dry Time**	1 Hour
Total Solids (by weight)	As mixed 100%
(by volume)	100%
Elongation	350% (ASTM D-2370)
Tensile Strength	200 psi (ASTM D-2370)
VOC Content	0g/L (0.0 lbs./gal)

### Manufacturer:

Conklin Company Inc.  
551 Valley Park Drive  
Shakopee, Minnesota 55379  
(800) 888 – 8838 Fax (952) 496 - 4285

### Product Description:

**Basic use:** Acclaim Pond B Gone™ is a two part self-leveling urethane slope corrector designed to address low-lying roof areas. Pond B Gone can be used prior to the application of Conklin's acrylic or urethane coating products for use over metal, BUR, modified bitumen membranes, SPF, ISO board, and concrete.

**Limitations:** Must not be applied at temperatures below 40°F or during inclement weather. Surface temperature must be at least 5°F above dew point and relative humidity less than 80 percent to ensure dry surfaces. Mix thoroughly before use. Ambient temperature should not exceed 100°F and surface temperature should not exceed 120°F. Acclaim Pond B Gone material must be 60°F or above to mix properly. The surface must be free of ponding water.

**Sizes:** Available in a 2 gallon kit.

**Coverage Rate:** Acclaim Pond B Gone can be applied up to an inch thick in a single application. If greater thickness is required allow an hour between applications.

\*\*Dry time for Acclaim Pond B Gone will vary depending on temperature, humidity, thickness at which the product is applied.

### Application:

**Mixing/thinning:** Always mix Acclaim Pond B Gone thoroughly before use. Smaller container of part A (1 gallon container) must be poured in to larger container of part B (3 1/2 gallon container) before mixing.

**Surface Preparation:** The substrate must be structurally sound, solid, clean and dry. On certain decks and surfaces, proper installation of drains, vapor retarders, roofing vents, expansion joints, flashings, and positive slope to drain will be required.

The application surface must be finished, smooth and free of grease, wax, dirt, contaminants, moisture and other matter that would interfere with adhesion. It must also be free of chips loose roofing or other foreign matter.

# ACCLAIM POND B GONE™

## Two Part Urethane Slope Correction

**Application:** For best results ensure surface is dry. Acclaim Pond B Gone can be applied up to an inch thick in a single application. Allow for 25 percent expansion. If more than an inch of depth is required allow an hour between lifts. When correcting low areas on PVC, TPO, and EPDM the membrane should be cut and peeled back or removed (terminations fastened as appropriate), Acclaim Pond B Gone applied to the acceptable substrate beneath, allowed to set up, and then coatings applied. Acclaim material temperature should be at 70°F-75°F for best mixing of A and B. Pour all of the A material into B before mixing. Mix with a stir stick for 30-45 seconds. Pour all mixed material in to the desired area immediately. Use a brush or plastic trowel to feather the edges.

### Clean Up:

While coating is still wet, clean tools and the area with xylene.

### Disposal:

Dispose of product in accordance with local state and federal regulations governing hazardous waste.

### Safety:

**Warning:** HARMFUL IF SWALLOWED. May cause eye, skin and respiratory system irritation. Keep out of the reach of children. If spraying use a NIOSH-approved dust/mist mask.

**First Aid:** Eyes – immediately flush with plenty of water for at least 15 minutes. If a contact lens is present, **DO NOT** delay irrigation or attempt to remove the lens until flushing is complete. Skin – wash with soap and water, followed by a thorough rinse. Ingestion – if swallowed, **DO NOT INDUCE VOMITING**, dilute with three to four glasses of water. Immediately call a Poison Control Center or physician for further instructions. Inhalation – immediately move to fresh air.

For US Health Hazard Information, call:

### Storage:

Keep containers tightly closed when not in use. Store in a cool place, above 40° F. Keep from freezing.

**Please Note:** *Previous field-applied coatings and residential properties are not warrantable.*

### Safety:

**Warning:** HARMFUL IF SWALLOWED. May cause eye, skin and respiratory system irritation. Keep out of the reach of children. If spraying use a NIOSH-approved dust/mist mask.

**First Aid:** Eyes – immediately flush with plenty of water for at least 15 minutes. If a contact lens is present, **DO NOT** delay irrigation or attempt to remove the lens until flushing is complete.

### Skin

– wash with soap and water, followed by a thorough rinse. Ingestion – if swallowed, **DO NOT INDUCE**

**VOMITING**, dilute with three to four glasses of water. Immediately call a Poison Control Center or physician for further instructions. Inhalation – immediately move to fresh air.

For US Health Hazard Information, call:

**1-888-786-0974**

**Proposition 65 Statement:** This product contains chemicals known to the State of California to cause cancer.

