

WAUSH OFF™

General Purpose Roof Cleaner

Wash Off™ is a general purpose cleaner formulated specifically to clean and maintain weathered roof coatings, including Conklin acrylic roof coatings, single-ply membranes, modified bitumen, and EPDM roofs.

- **Thoroughly cleans surface**
- **Leaves no residue**
- **Restores aged surfaces to like-new finish**

COVERAGE: One gallon of Wash Off will clean approximately 400 to 500 square feet, depending on surface condition.

SURFACE PREPARATION: Before cleaning, all surfaces must be completely dry, and free of debris.

LIMITATIONS: Avoid roof run-off while cleaning with Wash Off to minimize possible staining of walls.

APPLICATION: Wet the roof surface thoroughly with water. Then apply Wash Off at full strength - DO NOT DILUTE. Apply with a brush, roller, or spray. May use conventional airless sprayer or portable tank sprayer. Scrub roof with a stiff bristle brush or broom to remove dirt, especially in stubborn areas and low spots. Leave Wash Off on the roof surface for a minimum of 20 minutes, then rinse with water using high pressure spray. Remove all debris and residue. Allow roof to dry completely. Repeat as necessary for complete roof cleanup.

CLEAN-UP: Clean tools with water.

STORAGE: Keep product from freezing.

DISPOSAL: Dispose of contents and empty containers according to local, state and federal regulations governing hazardous waste. Keep out of trash, water, sewer, and drainage systems.

WARNING:

May cause irritation to eyes, skin, and digestive system.

PRECAUTIONS: Avoid breathing mist, vapors, and spray. Use in a well ventilated area. Do not eat, drink or smoke when using this product. Wear gloves, safety glasses or goggles, and long-sleeved clothing when handling concentrate. Rinse hands thoroughly after handling.

RESPONSE/FIRST AID: May cause eye irritation. If adverse effect occurs, flush eyes with water. May cause skin irritation. If adverse effect occurs, flush skin with water. May cause upset stomach. Drink plenty of water to dilute. May cause respiratory irritation. If adverse effect occurs, move to fresh air. If irritation persists, seek medical attention.

CONTAINS: Biodegradable surfactants

For US Health Hazard Information, call 1-888-786-0974.

VOC Concentration: 0 g/L



Conklin Company Inc.
Roofing Systems Division
551 Valley Park Drive
Shakopee, MN 55379
www.ConklinRoofingSystems.com

**Net Contents:
5 US Gallons (9.5 L)**

